

Technical Product Information



CESA™ Clariclean 9105P PEA0407038

Description	Processing of thermoplastic polymers needs a periodic complete elimination of thermo-oxidized deposits from extruders and injection moulding barrels and screws. This process prevents contamination of finished products. Addition of CESA™ clean masterbatches reduces the lead time when cleaning, colour and/or polymer change is required.
Physical form	CESA™ Clariclean 9105P is a cleaning agents in a polyethylene carrier
Applications	Purging of injection moulding, film extrusion, blow moulding etc. Processing of LDPE, LLDPE, EVA, HDPE and PP. Cleaning of barrels, dies etc. when a quick change of colour or polymer is required
Typical properties	Reduction in cleaning time Excellent cleaning
Dosage	Use 100% MB. Set the temperature on machine and tools at somewhat higher temperature (10 degrees) than for the Thermoplastic you are cleaning out. Run Clariclean 9105 P until it has filled up all internal parts of machine and tools. Then stop the machine. Allow machine to stand still under heat for 10 minutes. Start machine again and run until clean.
Packaging	25 kg woven sack bags
Remarks	The product should be stored in a cool and dry place, away from direct sunlight. Under proper storage condition the product can be stored for 12 months.

AVIENT WORLDWIDE CONTACT INFORMATION

<http://www.avient.com/contact/global-directory-and-contacts>

January 2021

Copyright © 2020, Avient Corporation. Avient makes no representations, guarantees, or warranties of any kind with respect to the Information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the Information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the Information. Avient makes no warranties or guarantees respecting suitability of either Avient's products or the Information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the Information and/or use or handling of any product. AVIENT MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the Information or products reflected by the Information. This data sheet shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.
