N1 000 UF BLK POLYAMIDE (PA-6)



PRODUCT DESCRIPTION

Nylon 6 Unfilled Black

FEATURES

- Excellent Mechanical & Chemical properties
- Injection Molding grade

APPLICATIONS

- Furniture
- Automotive
- Home appliance

TYPICAL PROPERTIES PHYSICAL PROPERTIES	TEST METHOD	UNIT	TYPICAL VALUES
Density	D-792	g/cc	1.14
MECHANICAL PROPERTIES			
Tensile Strength	D-638	MPa	70
Elongation Break	D-638	%	25
Flexural Strength	D-790	MPa	90
Impact Strength (IZOD Notched)	D-256	Kg cm/cm	7
THERMAL PROPERTIES			
Heat Deflection Temperature - Method B	D-648	°C	60

Ravago Manufacturing India Private Limited.





TEST U	UNIT TYPICAL
METHOD	VALUES
UL 94	- HB
IEC 60695-	NA
IEC 60695- 2-12	

INJECTION MOLDING CONDITIONS		
Mold Temperature	°C	80 to 100
Rear Temperature	°C	220 to 230
Middle Temperature	°C	230 to 240
Front Temperature	°C	240 to 250
Nozzle Temperature	°C	235 to 240

Drying Conditions

Material can be dried for 4 hours at 100 - 110°C or until moisture level <0.2%.

HANDLING AND STORAGE

Handling: Maintain good housekeeping. Spilled materials may create a slipping hazard. Remove dust from settling areas to prevent any secondary potential dust explosion or fire hazards. Electrostatic charge may build up during handling. Grounding of equipment is recommended.

Storage: Store in a dry place and away from direct sunlight or heat sources.

DISPOSAL CONSIDERATIONS

Disposal Method: It must be disposed of in accordance with Federal, State and local environmental control regulations.

The data and information contained herein are typical average values, based on our current level of knowledge and experience, and do not constitute sales specifications. No liability, warranty or guarantee of product performance is created by this document. It is the buyer's responsibility to inspect and test our products in order to determine the suitability for the buyer's application.

Ravago Manufacturing India Private Limited.

96, GIDC Alindra, Manjusar, Tal. Savali, Vadodara 391775. India +919909901581 Format No: F-QC-20

echnical Datashee

